

SMITTYBILT

NEWS

Class SB2 | Issue 13 | September 2008 | Product Highlight: 8,000lb Winch | www.smittybilt.com

NEW PRODUCT



Smittybilt XRC-8 Winch

The new Smittybilt XRC-8 Winch encompasses all the best features you would want in a winch. Every XRC-8 (8,000 LB.) winch features a 5.5HP Series Wound Motor and a Planetary Gear System with 172.8:1 gear ratio that will deliver power and reliability at a premium price. For a recovery system with the muscle and dependability to bail you out of any situation, the XRC-8 has all the heavy duty toughness you're looking for.

XRC 8 Specifications

- Rated Line Pull:** 8000Lbs (3600kgs) single-line
- Motor:** 5.5hp Series Wound
- Control:** Remote Switch, 12' (3.7m) lead
- Gear Train:** 3-Stage Planetary
- Gear Ratio:** 172.8:1
- Clutch:** Rotating Ring Gear
- Brake:** Automatic In-The-Drum
- Drum Size:** Diameter 2.5" (63.5mm) Length 8.82" (224mm)
- Wire Rope:** 94' 21/64" Diameter (28.5m, 8.2mm Diameter)
- Fairlead:** 4-Way Roller
- Remote Control:** Included
- Recommended Battery:** 650CCA Minimum for Winching
- Battery Leads:** 25mm², 72" (1.83m)1
- Finish:** Black
- Weight:** 94.0Lbs (42.5Kgs)
- Mounting Bolt Pattern:** 10.0x4.50

8LB
8000LB PULL

5.5
HORSE POWER

GA
GALVANIZED CABLE

172
172:1 GEAR RATIO

EZ
INSTALL



(A)



(B)



(C)

- A) Remote
- B) Roller Fairlead
- C) Hook

LINE SPEED & AMP DRAW-FIRST LAYER

Line Pull	Lbs	NO LOAD				
	Kgs	2000	4000	6000	8000	
Line Speed	Fpm	37.2	18	13.1	10.2	8.2
	Mpm	11.4	5.5	4.1	3.2	2.6
Motor current	amps	75	195	260	335	410

LINE PULL & CABLE CAPACITY

Layer of Cable		1	2	3	4
Rate line pull per layer	Lbs	8000	6900	5850	5100
	Kgs	3630	3130	2650	2310
Cable capacity per layer	Ft	16	42	72	94
	Mpm	5	12	21	28

1.888.717.5797

400 West Artesia Blvd., Compton, CA 90220

www.smittybilt.com

